POWER DISTRIBUTION BOARD VERTICAL - 45RU - 03203-64



PCB Mounted 10A AUS Outlet Socket 240V AC - 50Hz single phase

Metalwork assembled

Front - 1.0mm Galvaneal Steel Powder Coat Black Sable

Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	03202-64
Input Voltage	240V AC
Input Current (Phase)	10A
Max Input Power	2400 watts
Input Phases	Single Input
Input Type	AUS Outlet Screw Lock Plug 10A 3 Flat Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 10A Reset Overload Protection
Outlet Type	10A AUS Outlet (AS3112)
Outlet Quantity	24
Outlet Colour	Black
Fittings Supplied	M5x10 screws and washers x4

DIMENSIONS	
Dimensions	1998mm L x 44mm W x 48mm D
Weight	3.3kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack



Screw Lock Plug 10A 3 Flat Pin (AS3112)