

POWER DISTRIBUTION BOARD

VERTICAL - 39RU - 93500-154



PCB Mounted 15A AUS Outlet Socket 240V AC - 50Hz single phase

Metalwork assembled
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable
 Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	93500-154
Input Voltage	240V AC
Input Current (Phase)	15A
Max Input Power	3600 watts
Input Phases	Single Input
Input Type	Lead mould fit - AUS Outlet GPO 15A 3 Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 15A Reset Overload Protection
Outlet Type	15A AUS Outlet (AS3112)
Outlet Quantity	18
Outlet Colour	Black
Fittings Supplied	M5x10 screws and washers x4



Aus Outlet GPO 15A Plug 3 Flat Pin (AS3112)

DIMENSIONS	
Dimensions	1734mm L x 44mm W x 48mm D
Weight	2.6kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack

