

POWER DISTRIBUTION BOARD

HORIZONTAL - 1RU - 19" RACK MOUNT - 93500-168



PCB Mounted 15amp AUS Outlet Socket 240V AC - 50Hz single phase
 Metalwork assembled - 1.0mm Galvaneal Steel Powder Coat Black Sable (Textured)

SPECIFICATIONS	
Part No	93500-168
Input Voltage	240V AC
Input Current (Phase)	15A
Max Input Power	3600 watts
Input Phases	Single Input
Input Type	Lead mould fit AUS Outlet 15A GPO 3 Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 15A Reset Overload Protection
Outlet Type	15A AUS Outlet (AS3112)
Outlet Quantity	6
Outlet Colour	Black
Fittings Supplied	M6 Rack Studs x4

DIMENSIONS	
Dimensions	19" Rackmount 483mm L x 44mm H x 100mm D Recessed
Weight	1.2kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to Website
Installed	Fitted to customer specified position in Server Rack



Aus Outlet GPO
 15A Plug 3 Flat Pin (AS3112)