

# POWER DISTRIBUTION BOARD

## VERTICAL - 18RU - 93500-160



### PCB Mounted 10A AUS Outlet Socket 240V AC - 50Hz single phase

Metalwork assembled

Front - 1.0mm Galvaneal Steel Powder Coat Black Sable

Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	<b>93500-160</b>
Input Voltage	<b>240V AC</b>
Input Current (Phase)	<b>15A</b>
Max Input Power	<b>3600 watts</b>
Input Phases	<b>Single Input</b>
Input Type	<b>AUS Outlet Screw Lock Plug 15A 3 Flat Pin (AS3112)</b>
Lead Length	<b>2.5M - Black</b>
Control Function	<b>Circuit Breaker 15A Reset Overload Protection</b>
Outlet Type	<b>10A AUS Outlet (AS3112)</b>
Outlet Quantity	<b>6</b>
Outlet Colour	<b>Black</b>
Fittings Supplied	<b>M5x10 screws and washers x4</b>



Screw Lock Plug 15A 3 Flat Pin (AS3112)

DIMENSIONS	
Dimensions	<b>800mm L x 44mm W x 48mm D</b>
Weight	<b>1.3kgs</b>
Country of Manufacture	<b>Australia</b>
Compliance	<b>AS/NZS 3100:2022</b> (General Requirements for Electrical equipment) <b>AS/NZS 3000:2018</b> (Electrical installations - wiring rules) <b>Designed to be installed in 19" Server Racks</b>
Packaging	<b>Sealed Plastic Bag</b>
Assembly Instructions	<b>Refer to website</b>
Installed	<b>Fitted to customer specified position in Server Rack</b>

