

POWER DISTRIBUTION BOARD

HORIZONTAL - 2RU - 19" RACK MOUNT - 93500-43



PCB Mounted 10A AUS Outlet Socket 240V AC - 50Hz single phase
Metalwork assembled - 1.0mm Galvaneal Steel Powder Coat Black Sable (Textured)

SPECIFICATIONS	
Part No	93500-43
Input Voltage	240V AC
Input Current (Phase)	15A
Max Input Power	3600 watts
Input Phases	Single Input
Input Type	AUS Outlet Screw Lock Plug 15A 3 Flat Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 10A Reset Overload Protection
Outlet Type	10A AUS Outlet (AS3112)
Outlet Quantity	10
Outlet Colour	Black
Fittings Supplied	M6 Rack Studs x4

DIMENSIONS	
Dimensions	19" Rackmount 483mm L x 88mm H x 100mm D Recessed
Weight	1.6kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to Website
Installed	Fitted to customer specified position in Server Rack



Screw Lock Plug
15A 3 Flat Pin (AS3112)