

POWER DISTRIBUTION BOARD

VERTICAL - 45RU - 93500-373



PCB Mounted 10A AUS Outlet Socket 240V AC - 50Hz single phase

Metalwork assembled
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable
 Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	93500-373
Input Voltage	240V AC
Input Current (Phase)	10A
Max Input Power	2400 watts
Input Phases	Single Input
Input Type	AUS Outlet Screw Lock Plug 10A 3 Flat Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 10A Reset Overload Protection
Outlet Type	10A AUS Outlet (AS3112)
Outlet Quantity	24
Outlet Colour	Black
Fittings Supplied	M5x10 screws and washers x4



**Screw Lock Plug
10A 3 Flat Pin (AS3112)**

DIMENSIONS	
Dimensions	1998mm L x 44mm W x 48mm D
Weight	3.3kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack

