

# POWER DISTRIBUTION BOARD

## VERTICAL - 39RU - 93500-377



### Wired 20A AUS Outlet Round White 240V AC - 50Hz single phase

Metalwork assembled  
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable  
 Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	<b>93500-377</b>
Input Voltage	<b>240V AC</b>
Input Current (Phase)	<b>20A</b>
Max Input Power	<b>4800 watts</b>
Input Phases	<b>Single Input</b>
Input Type	<b>AUS Outlet Screw Lock Plug 20A 3 Flat Pin (AS3112)</b>
Lead Length	<b>2.5M - Black</b>
Control Function	<b>Circuit Breaker 20A Reset Overload Protection</b>
Outlet Type	<b>20A AUS Outlet (AS3112)</b>
Outlet Quantity	<b>18</b>
Outlet Colour	<b>White</b>
Fittings Supplied	<b>M5x10 screws and washers x4</b>



**Screw Lock Plug 20A 3 Flat Pin (AS3112)**

DIMENSIONS	
Dimensions	<b>1734mm L x 44mm W x 48mm D</b>
Weight	<b>2.6kgs</b>
Country of Manufacture	<b>Australia</b>
Compliance	<b>AS/NZS 3100:2022</b> (General Requirements for Electrical equipment) <b>AS/NZS 3000:2018</b> (Electrical installations - wiring rules) <b>Designed to be installed in 19" Server Racks</b>
Packaging	<b>Sealed Plastic Bag</b>
Assembly Instructions	<b>Refer to website</b>
Installed	<b>Fitted to customer specified position in Server Rack</b>

