

POWER DISTRIBUTION BOARD

VERTICAL - 18RU - 93500-380



Wired 20A AUS Outlet Round White 240V AC - 50Hz single phase

Metalwork assembled
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable
 Rear- Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	93500-380
Input Voltage	240V AC
Input Current (Phase)	20A
Max Input Power	4800 watts
Input Phases	Single Input
Input Type	Lead - AUS Outlet GPO 20A 3 Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 20A Reset Overload Protection
Outlet Type	20A AUS Outlet Round White (AS3112)
Outlet Quantity	8
Outlet Colour	White
Fittings Supplied	M5x10 screws and washers x4



Aus Outlet GPO
 20A Plug 3 Flat Pin (AS3112)

DIMENSIONS	
Dimensions	800mm L x 44mm W x 48mm D
Weight	1.3kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack

