

POWER DISTRIBUTION BOARD

VERTICAL - 39RU - 93500-382



Wired 20A AUS Outlet Round White 240V AC - 50Hz single phase

Metalwork assembled
 Front - 1.0mm Galvaneal Steel Powder Coat Black Sable
 Rear - Aluminium Extrusion - Black Anodised

SPECIFICATIONS	
Part No	93500-382
Input Voltage	240V AC
Input Current (Phase)	20A
Max Input Power	4800 watts
Input Phases	Single Input
Input Type	Lead - AUS Outlet GPO 20A 3 Pin (AS3112)
Lead Length	2.5M - Black
Control Function	Circuit Breaker 20A Reset Overload Protection
Outlet Type	20A AUS Outlet Round White (AS3112)
Outlet Quantity	18
Outlet Colour	White
Fittings Supplied	M5x10 screws and washers x4



Aus Outlet GPO
 20A Plug 3 Flat Pin (AS3112)

DIMENSIONS	
Dimensions	1734mm L x 44mm W x 48mm D
Weight	2.6kgs
Country of Manufacture	Australia
Compliance	AS/NZS 3100:2022 (General Requirements for Electrical equipment) AS/NZS 3000:2018 (Electrical installations - wiring rules) Designed to be installed in 19" Server Racks
Packaging	Sealed Plastic Bag
Assembly Instructions	Refer to website
Installed	Fitted to customer specified position in Server Rack

